K9S
BELTED VACUUM CHAMBER MACHINE



SCAN TO SEE THE K9 IN ACTION

MADE IN SWITZERLAND



BI-ACTIVE SEALING BARS

- Quick and safe sealing even with thick creases, grease or product liquids
- Bi-active* sealing bars with electronic temperature control and precisely controlled contact pressure

*bi-active = from the top and bottom



CONVEYOR BELT

- Easy clamp and release belt for fast cleaning
- Frequency-controlled belt to regulate conveyor speed smoothly and adjust start/stop pads in selected position



TRIM REMOVAL

- Optional: Extracts bag trims directly into trim collector unit installed on both sides

FEATURES

- Automatic indexing conveyor allows user to pre-load product during vacuum cycle for continuous production
- Compact hygienic design easy to clean all stainless construction
- Open construction allows for easy cleaning and maintenance
- Programmable settings to store configured settings as formulas for future use
- Programmable vacuum control for precise evacuation to the evaporation point, with optional stepwise vacuum adjustment to the desired set point
- Bi-active sealing bars with electronic temperature control and contact pressure to ensure quick and safe sealing
- High-quality seal creates a strong seal on all bag types
- Pre-perforation allows for use of longer bags
- Automatic lid with 3kW spur gear motor (no compressed air needed)



K9S CONTROL UNIT

- High resolution color display, screen size 8” with multiple language options
- Can be operated from both sides of the machine
- Simple to control and program via soft keys
- Remote maintenance possible via standard interfaces (depends on customer’s infrastructure)

ADD A SHRINK TUNNEL & DRYER FOR A COMPLETE PACKAGING LINE



MACHINE SPECS	
MACHINE STYLE	Single Chamber
NUMBER OF SEAL BARS	2
SEAL BAR LENGTH	1500 mm / 59 in
CHAMBER DIMENSIONS	1500 x 910 x 285 mm 59 x 35.8 x 11.2 in
VACUUM PUMP	*Options available*
MACHINE DIMENSIONS	4391 x 1330 x 1700 mm 172.9 x 52.4 x 66.9 in
DISTANCE BETWEEN SEAL BARS	900 mm / 35.4 in
MACHINE CONTROLS	Digital / Programmable
MACHINE WEIGHT	1720 kg / 3792 lbs
ELECTRICAL CONNECTION	400 V / 3 Ph / 50 Hz 440 V / 3 Ph / 60 Hz (Optional)
GAS FLUSH	Optional

K9S MACHINE RUNS: FLEXIBLE AND SHRINK PACKAGING TYPES





Tell us your vision and we will build a custom solution for you! Email us at Sales@VC999.com

UNITED STATES: Sales@VC999.com
North Kansas City - 1 800-728-2999

CENTRAL/SOUTH AMERICA: Sales.Americas@VC999.com
1-800-728-2999

COLOMBIA: Sales.Colombia@VC999.com
57 (1) 8966546 or 8966798

CANADA: Sales.Canada@VC999.com
Montreal - 1 819-395-4555

MEXICO: Sales.Mexico@VC999.com
Monterrey - 52 81 8361 3178
Mexico City - 52 55 5876 7784

VC999®
www.VC999.com
PACKAGING plus+